



## ELECTRIC HEATERS - 1.5 KW THRU 150 KW

Forced-air electric heaters set the standard for heavy-duty portable electric heat. They feature rugged steel jacketed heating element construction, a powder coated steel housing, a high-quality sealed motor, UL/CSA approved. Each unit is equipped with overheat protection and the heating element stays cool even when the heater is running. They are capable of a very quick and high temperature rise, with the industrial-grade fan distributing warm powerful air. They come in various voltages to accommodate your electrical power supply.

EQUIPMENT MODEL	CAPACITY HEATING	KW	VOLTAGE /PHASE	RUN AMPS	DUCTABLE (LENGTH)	CFM	DIMENSIONS (L x W x H)	WEIGHT (LBS)	PLUG TYPE
E1.5/P1500	5,100	1.5	120/1	12.5	N	116	13 x 17.5 x 11	14/16	5-15P
E3/P300	10,200	3.0	240/1	12.5	N	205	12 X 10 X 15	20/22	6-20P
E6/P600	20,500	6.0	240/1	25.0	N	250	19.5 x 11.8 x 17.3	33/40	14-30P
E9/P900	30,700	9.0	240/1	38.0	N	350	22 x 18 x 12	48/51	14-50P
FES-1024-1CA	34,130	10.0	240/1	42.0	N	800	21.0 x 27.0 x 39	60/69	14-50P
FES-1524-3E	51,195	15.0	240/3	36.0	N	800	21.0 x 27.0 x 39	69/78	Wired
18E-1/P1800-1	65K/41K	18/12	240/1	75/50	N	590	30 x 14 x 20	62/65	Wired
18E-3/P1800-3	65K/41K	18/12	240/3	50/34	N	590	30 x 14 x 20	62/65	Wired
1800D	65K/41K	18/12	240/3	50/34	12" X 50'	940	30 x 14 x 20	62/65	Wired
FES-3048-3A	102,390	30.0	480/3	36.0	N	1100	23.0 x 27.0 x 39	83/95	Wired
40E/P4000	136,500	40.0	480/3	48.0	14" X 50'	1800	46 x 20 x 25	130/140	Cam
FES-4548-3	153,585	45.0	480/3	55.4	N	2200	45.5 x 23.3 x 39	198/210	Wired
60E/P6000	204,700	60.0	480/3	72.0	14" X 50'	1800	46 x 20 x 25	142/155	Cam
EB60E	136,500/204,700	60/40	240/480/3	144/72	12" X 50'	4500	22 x 51.5 x 35.5	300	Cam
EB150E	512,000	150.0	480/3	180/108/72	20" X 200'	14,500	32 x 68 x 56	950	Cam

Forced-air electric heaters, FireBird, come in a stainless-steel cabinet which can be ducted. A variety of heat outputs are sustainable through different stages of heat.

EQUIPMENT MODEL	CAPACITY HEATING	VOLTAGE /PHASE	RUN AMPS	DUCTABLE	CFM	DIMENSIONS (L x W x H)	WEIGHT (LBS)	PLUG TYPE
Firebird Compact 20	20,000	120/1	12 (X) 4 CKT	Y	250	13 x 12.5 x 26	21/35	5-15P
Firebird	18,000/31,000	240/1	30 or 50	Y	360	20.3 X 40 X 21.4	90/115	14-30P or 14-50P

### PLUG CONFIGURATION




5-15P



6-20P



14-30P



14-50P

### CAMLOCK CONNECTORS AVAILABLE



CAM-LOCK CABLE



CAM-LOCK TAIL

Call (888)519-1422 On Call 24/7

Serving the Midwest

EMAIL: [info@porta-air.com](mailto:info@porta-air.com)

[www.porta-air.com](http://www.porta-air.com)

