



## DEHUMIDIFIERS

Dehumidifiers come in both Desiccant and LGR. They range from standard plug in the wall to industrial strength. Depending on the amount of moisture removal and ambient temperature, certain dehumidifiers do a better job than others. Standard plugin the wall units are the most popular since standard outlets are almost always available. Offsite monitoring of the equipment can be accomplished through Bluetooth-enabled technology for certain models.

EQUIPMENT MODEL	AHAM RATING (PPD)	VOLT /PHASE	RATED AMPS	CFM PROCESS	OPERATING RANGE	PLUG TYPE	DIMENSIONS W x H x D	WEIGHT/ SHIPPING
DryMAX BLE	80	115/1	5.7	170	33F-110F	5-15P	12 x 17.5 x 21	63/65
DryMAX XL	125	115/1	7.7	300	33F-110F	5-15P	16 x 17.5 x 24	88/90
R250	135	115/1	8.3	310	33F-110F	5-15P	20 x 33.5 x 20	109/119
250 MAX	145	115/1	8.2	365	33F-125F	5-15P	20 x 40 x 23	119/137
D385	130	115/1	11(X)2	385	-10F-140F	5-15P(X)2	24.3 x 40 x 21.4	105/130
DH600	240	460/3	12	600	-4F-104F	CAM LOCK	22 x 43 x 29	206
D850	370	230/1	24 or 40	850	-10F-140F	14-30P/14-50P	20 x 41 x 23.3	155/173
TR390	390	460/3	15	853	-4F-104F	HARD WIRE	25 x 37 x 26	221
TR570	571	460/3	23	1175	-4F-104F	HARD WIRE	30 x 52 x 53	507
TR830	830	460/3	31.7	1648	-4F-104F	HARD WIRE	30 x 52 x 53	551
TR1100	1084	460/3	42.8	2177	-4F-104F	HARD WIRE	30 x 52 x 53	595
DH2250	1320	460/3	52.0	2250	-4F-104F	CAM LOCK	29 x 58 x 89	1250
DH4500	2152	460/3	108.0	4500	-4F-104F	CAM LOCK	46 x 77 x 98	1950
DH5000(Electric)	2336	460/3	148.0	5000	-4F-104F	CAM LOCK	50 x 96 x 101	4400
DH5000 (Fuel)	2336	460/3	21.0	5000	-4F-104F	CAM LOCK	50 x 96 x 101	4400
DH7500(Electric)	2680	460/3	178.0	7500	-4F-104F	CAM LOCK	50 x 96 x 101	4400
DH7500 (Fuel)	2680	460/3	21.0	7500	-4F-104F	CAM LOCK	50 x 96 x 101	4400
DH15000 (Electric)	3536	460/3	345.0	15000	-4F-104F	CAM LOCK	100 x 101 x 140	9500
DH15000 (Fuel)	3536	460/3	55.0	15000	-4F-104F	CAM LOCK	100 x 101 x 140	9500

Call (888)519-1422 On Call 24/ 7

Serving the Midwest

EMAIL: [info@porta-air.com](mailto:info@porta-air.com)

[www.porta-air.com](http://www.porta-air.com)

