



DESICCANT DEHUMIDIFIER SPECIFICATIONS: Desiccant Dehumidifiers remove high rates of humidity from the air at a wide range of temperatures, well below freezing. All units are equipped with a regeneration side which evaporates the collected moisture from the desiccant wheel and the hot air rejects the moist air through ductwork. Therefore, a condensate pump is not required. Units are rated at AHAM conditions of 80° F DB/60% RH.

DESICCANT DEHUMIDIFIERS

STAINLESS STEEL CABINET

* - CROSS REFERENCE "ACCESSORY REF. NO." TO "COMMON ACCESSORY" PDF FOR DESCRIPTION AND PART NUMBER DETAIL

MODEL	PART NUMBER	VOLTS	AMPS	PH	PROCESS AIR FLOW CFM	FILTER SIZE/TYPE	REACTIVATION AIRFLOW CFM	AHAM RATING* PINTS PER DAY (PPD)	OPERATING RANGE	DIMENSIONS			SHIPPING DIMENSIONS			WEIGHT (LBS)	SHIPPING WEIGHT (LBS)	*ACCESSORY REF. NO.
										W	H	D	W	H	D			
D385	4026700	115	11 EA. 2 CIRCUITS	1	385	Pleated 16" x 20" x 2" Media MERV-11 (Process) Pleated 12" x 12" x 1" Media MERV-11 (Reactivation)	75	130	-10° F TO 140° F	24.3	40	21.4	27.5	45.5	22	105	130	71, 79, 74, 65A, 65, 100, 3, 26, 27, 63A, 31, 32, 33
D850	4034000	208/230	24 OR 40	1	850	Pleated 20" x 20" x 2" Media MERV-11 (Process) Pleated 9" x 11 3/8" x 1/4" Media MERV-11	225	370	-10° F TO 140° F	20	41	23.3	24	47	26	155	173	71, 79, 74, 77, 65A, 65, 101, 100, 93, 94, 94A, 94B, 102, 11, 36
TR390	4041630	480	15	3	853	12" X 12" X 2"	158	390	-4°F to 104°F	24.6	37	25.6				221		63H, 63I, 63J, 63K, 63L
TR570	4041640	480	23	3	1175	12" X 12" X 2"	225	571	-4°F to 104°F	30	52	53				507		63H, 63N, 63M, 63J, 63L, 63O

Call 888-519-1422 On Call 24/ 7

Serving the Midwest

EMAIL: info@porta-air.com

www.porta-air.com

