



ELECTRIC HEATER SPECIFICATIONS: Heat aids in the drying process. When the air is heated, it allows more water vapor to be carried by the air thus moisture is removed quickly from your space, avoiding mold issues. The Firebird, compact 20 is a unique unit since it can deliver 20,000 Btu's on 115 V circuits avoiding the need for a 220 V hookup. On the other hand, the Firebird can be hooked up to range or stove power which delivers different heating outputs.

ELECTRICAL HEATERS

* - CROSS REFERENCE "ACCESSORY REF. NO." TO "COMMON ACCESSORY" PDF FOR DESCRIPTION AND PART NUMBER DETAIL

MODEL	PART NUMBER	VOLTS	AMPS	PH	CFM	FEATURES	BTU'S/HR	DIMENSIONS			SHIPPING DIMENSIONS			WEIGHT (LBS)	SHIPPING WEIGHT	*ACCESSORY REF. NO.
								W	H	D	W	H	D			
FIREBIRD COMPACT 20	4033450	115	12/CIRCUIT	1 PH 4 CIRCUITS	250	Remote Thermostat, Stainless Steel Cabinet, Ductable, Filtered Air	20,000	13	12.5	26	17	17	30	21	35	48, 72, 99, 38, 39, 103, 61
FIREBIRD	4027300	240	30/50	1	360	Remote Thermostat, Stainless Steel Cabinet, Ductable, Filtered Air	18,000/31,000	20.3	40	21.4	27.5	45.3	25.5	90	115	74, 26, 3, 63A, 93, 103, 100, 94B, 93, 94, 94A, 63C

Call 888-519-1422 On Call 24/ 7
Serving the Midwest
EMAIL: info@porta-air.com
www.porta-air.com

