



LGR DEHUMIDIFIER SPECIFICATIONS: LGR Dehumidifiers remove humidity from the air under normal working conditions. All portable units are equipped with long extension cords, and condensate pumps. All units operate off of 115 V standard power and are equipped with a standard 5-15 plug. Units are rated at AHAM conditions of 80° F DB/60% RH.

LGR DEHUMIDIFIERS

PLASTIC MOLDED CABINET

* - CROSS REFERENCE "ACCESSORY REF. NO." TO "COMMON ACCESSORY" PDF FOR DESCRIPTION AND PART NUMBER DETAIL

MODEL	PART NUMBER	AMPS	PH	CFM	FILTER SIZE/TYPE	AHAM RATING* PINTS PER DAY (PPD)	OPERATING RANGE	DIMENSIONS			SHIPPING DIMENSIONS			WEIGHT (LBS)	SHIPPING WEIGHT	*ACCESSORY REF. NO.
								W	H	D	W	H	D			
DryMAX	4036000	5.7	1	170	Pleated 9"x12"x1" MERV-10	80	33° F TO 110° F	12	17.5	21	16	19	35	63	65	67, 49, 50, 51
DryMAX Blue	4036060	5.7	1	170	Pleated 9"x12"x1" MERV-10	80	33° F TO 110° F	12	17.5	21	16	19	35	63	65	54, 55, 65, 67, 74, 51
R150	4031250	5.5	1	150	Pleated 12" x 12" x 1" MERV-8	75	33° F TO 110° F	20	30	17	20.5	35.25	18.63	82	93	74, 67, 65, 54
R175	4029200	6.3	1	230	Pleated 12" x 12" x 1" MERV-8	92	33° F TO 110° F	20	33.5	20	24	45.25	25.5	105	110	30, 31, 32, 65, 74, 28
DryMAX XL	4037000	7.7	1	300	12" x 14" x 1" MERV-10	125	33° F TO 110° F	16	17.5	23	16	17.5	23	88	90	65, 67, 54, 55, 74, 52, 53
DryMAX XL Blue	4037060	7.7	1	300	12" x 14" x 1" MERV-10	125	33° F TO 110° F	16	17.5	23	16	17.5	23	88	90	65, 67, 54, 55, 74, 52, 53
R250 R250	4034460 4035230	8.3	1	310	Pleated 12" x 12" x 1" MERV-11	135	33° F TO 110° F	20	33.5	20	21	35.25	21	109	119	30, 65, 74, 28

STAINLESS STEEL CABINET

MODEL	PART NUMBER	AMPS	PH	CFM	FILTER SIZE/TYPE	AHAM RATING* PINTS PER DAY (PPD)	OPERATING RANGE	DIMENSIONS			SHIPPING DIMENSIONS			WEIGHT (LBS)	SHIPPING WEIGHT	*ACCESSORY REF. NO.
								W	H	D	W	H	D			
250 MAX	4030010	8.2	1	365	Pleated 16" x 20" x 2" MERV-11	145	33° F TO 125° F	20	40	23	24	47	26	119	137	26, 27, 3, 74, 65
300 MAX	4030020	10	1	395	Pleated 16" x 20" x 2" MERV-11	175	33° F TO 125° F	20	40	23	24	47	26	130	148	74, 68, 26, 3

Call 888-519-1422 On Call 24/ 7

Serving the Midwest

EMAIL: info@porta-air.com

www.porta-air.com

