PORTA-AIR
Providing Emergency Rentals, Sales and Service...Anywhere
(888)519-1422

WATER-COOLED AC EQUIPMENT

Water cooled portables are the customers system of choice for enclosed areas with no windows, no means to ventilate hot exhaust air, or where floor space is minimal. This is type of cooling system is popular in restaurants, hospitals, taverns, labs, etc. OWC models are optional with Quick Connect (QC) hose adapters. 5WK models come standard with quick connect hose adapters. Longer hose kits are available.

EQUIPMENT MODEL	CAPACITY BTU	TON	VOLTAGE /PHASE	RUNNING AMPS	BREAKER AMPS	SOUND LEVEL	NEMA PLUG	DIMENSIONS W x D x H	WEIGHT/ SHIPPING
5WK07	6,300	0.5	115	9.2	15	-	5-15P	22.4 x 12 x 17.6	83/99
5WK14	10,400	0.9	115	11.6	15	-	5-15P	25 x 10.2 x 31.5	122/131
OWC/PWC 1211	12,000	1.0	115	8.1	15	52	5-15P	20.13 x 13.13 x 34	110/130
5WK18	16,100	1.3	208/230/1	6.6	15	-	6-20P	36 x 12.3 x 28.8	183/201
OWC/PWC 1811	18,000	1.5	115	11.3	15	57	5-15P	21.5 x 16 x 45.7	150/170
5WK26	23,000	1.9	208/230/1	10.0	20	-	6-20P	36 x 12.3 x 28.8	185/203
OWC/PWC 2412	23,950	2	208/230/1	9.9	20	60	6-20P	21.5 x 16 x 45.7	160/180
OWC/PWC 3612	36,100	3	208/230/1	12.0	20	62	6-20P	28.2 x 21.5 x 51	240/270
OWC/PWC 3632	36,100	3	208/230/3	9.3	20	62	L15-20P	28.2 x 21.5 x 51	240/270
OWC/PWC 3634	36,100	3	460/3	4.7	20	62	L16-20P	28.2 x 21.5 x 51	310/340
OWC/PWC 6012	60,100	5	208/230/1	23.7	30	69	6-30P	28.2 x 29.2 x 53.2	460/500
OWC/PWC 6032	60,100	5	208/230/3	16.5	30	69	L15-30P	28.2 x 29.2 x 53.2	460/500
OWC/PWC 6034	60,100	5	460/480/3	6.3	20	69	L16-20P	28.2 x 29.2 x 53.2	520/560

PLUG CONFIGURATION

5-15P 5-20P 6-20P 6-30P 6-50P L15-20P L15-30P L16-20P