



## **AIR COOLED EQUIPMENT 1 TON THRU 5 TON**

Air-cooled portables are the customers cooling system of choice for workplaces, computer room, classrooms, special events, hospitals, industrial and most comfort cooling applications. Service is the name of the game and air cooled equipment can be installed almost anywhere in a matter of minutes. Please call us today!

<b>MODEL</b>	<b>CAPACITY BTU TON</b>	<b>VOLTAGE /PHASE</b>	<b>RUNNING AMPS</b>	<b>BREAKER AMPS</b>	<b>SOUND LEVEL</b>	<b>NEMA PLUG</b>	<b>DIMENSIONS W x D x H</b>	<b>WEIGHT/ SHIPPING</b>
PAC1211	11,800 1.0	115	10.4	15	54	5-15	20 x 25 x 37	180/200
2OAC1211	11,800 1.0	115	10.4	15	54	5-15	20 x 25 x 37.75	180/200
CAC1211	12,000 1.0	115	12.0	15	-	5-15	17.5 x 24 x 20.25	135/150
PAC1811	16,800 1.4	115	14.1	20	60	5-20	24 x 30 x 44.5	260/285
2OAC1811	16,800 1.4	115	14.1	20	60	5-20	24 x 30 x 45.75	260/285
PAC2412	24,020 2.0	208/230/1	14.9	20	65	6-20	24 x 30 x 44.5	260/285
2OAC2412	24,020 2.0	208/230/1	14.9	20	65	6-20	24 x 30 x 45.75	260/285
PAC3612	36,050 3.0	208/230/1	19.6	30	69	6-30	27 x 35 x 50.25	365/405
PAC3632	36,050 3.0	208/230/3	17.2	30	69	L15-30	27 x 35 x 50.25	365/405
PAC3634	36,050 3.0	460/3	8.7	20	69	L16-20	27 x 35 x 50.25	380/420
2OAC3612	36,050 3.0	208/230/1	19.6	30	69	6-30	27.5 x 35 x 50.25	365/405
2OAC3632	36,050 3.0	208/230/3	17.2	30	69	L15-30	27.5 x 35 x 50.25	365/405
2OAC3634	36,050 3.0	460/3	8.7	20	69	L16-20	27.5 x 35 x 50.25	400/440
PAC6012	60,100 5.0	208/230/1	32.0	50	78	6-50	27 x 39.5 x 51.25	485/525
PAC6032	60,100 5.0	208/230/3	20.4	30	78	L15-30	27 x 39.5 x 51.25	485/525
PAC6034	60,100 5.0	460/3	14.8	20	78	L16-20	27 x 39.5 x 51.25	515/555
2OAC6012	60,100 5.0	208/230/1	32.0	50	78	6-50	27.5 x 39.5 x 51.75	485/525
2OAC6032	60,100 5.0	208/230/3	20.4	30	78	L15-30	27.5 x 39.5 x 51.75	485/525
2OAC6034	60,100 5.0	460/3	14.8	20	78	L16-20	27.5 x 39.5 x 51.75	520/560

## **WATER-COOLED EQUIPMENT 1 TON THRU 5 TON**

Water cooled portables are the customers system of choice for enclosed areas with no windows or means to ventilate hot exhaust air or where floor space is minimal. This is the system of choice for restaurants, hospitals, taverns, labs, etc. OWC models are optional with Quick Connect (QC) hose adapters.

<b>MODEL</b>	<b>CAPACITY BTU TON</b>	<b>VOLTAGE /PHASE</b>	<b>RUNNING AMPS</b>	<b>BREAKER AMPS</b>	<b>SOUND LEVEL</b>	<b>NEMA PLUG</b>	<b>DIMENSIONS W x D x H</b>	<b>WEIGHT/ SHIPPING</b>
OWC/PWC 1211	12,000 1.0	115	8.1	15	52	5-15	20.13 x 13.13 x 34	110/130
OWC/PWC 1811	18,000 1.5	115	11.3	15	57	5-15	24.25 x 13 x 40	150/170
OWC/PWC 2412	23,950 2	208/230/1	9.9	20	60	6-20	24.25 x 13 x 40	160/180
OWC/PWC 3612	36,100 3	208/230/1	12.0	20	62	6-20	28.25 x 18 x 50	240/270
OWC/PWC 3632	36,100 3	208/230/3	9.3	20	62	L15-20	28.25 x 18 x 50	240/270
OWC/PWC 3634	36,100 3	460/3	4.7	20	62	L16-20	28.25 x 18 x 50	270/300
OWC/PWC 6012	60,100 5	208/230/1	23.7	30	69	6-30	27 x 29 x 51.5	460/500
OWC/PWC 6032	60,100 5	208/230/3	16.5	30	69	L15-30	27 x 29 x 51.5	460/500
OWC/PWC 6034	60,100 5	460/480/3	6.3	20	69	L16-20	27 x 29 x 51.5	520/560

Call 888-519-1422 On Call 24/ 7

Serving the Midwest

EMAIL: [info@porta-air.com](mailto:info@porta-air.com)

[www.porta-air.com](http://www.porta-air.com)





## HEAT PUMP UNITS 1 TON THRU 5 TON

Air conditioning and heating in one system! Perfect for year-round use. Safe and convenient to install. Our air-cooled heat pumps supply 100% safe, efficient heat. They are very popular in office settings, where electric heaters may be a fire hazard.

MODEL	CAPACITY COOLING	CAPACITY HEATING	VOLTAGE /PHASE	RUNNING AMPS	BREAKER AMPS	NEMA PLUG	DIMENSIONS W x D x H	WEIGHT/ SHIPPING WT
2OACH1211	11,800	11,000	115/1	10.4	15	5-15	20 x 25 x 38	180/200
2OACH1811	16,800	15,600	115/1	14.1	20	5-20	24 x 30 x 46	260/285
2OACH2412	24,020	22,000	208/230/1	14.9	20	6-20	24 x 30 x 46	260/285
2OACH3612	36,050	32,500	208/230/1	19.6	30	6-30	27.5 x 35 x 50.25	365/405
2OACH3632	36,050	32,500	208/230/3	17.2	30	L15-30	27.5 x 35 x 50.25	365/405
2OACH3634	36,050	32,500	460/3	8.7	20	L16-20	27.5 x 35 x 50.25	400/440
2OACH6012	60,100	53,500	208/230/1	32.0	50	6-50	27.5 x 39.5 x 51.75	485/525
2OACH6032	60,100	53,500	208/230/3	20.4	30	L15-30	27.5 x 39.5 x 51.75	485/525
2OACH6034	60,100	53,500	460/3	14.8	20	L16-20	27.5 x 39.5 x 51.75	520/560

## PLUG CONFIGURATION



5-15P



5-20P



6-20P



6-30P



6-50P



L15-20P



L15-30P



L16-20P



Call 888-519-1422 On Call 24/ 7

Serving the Midwest

EMAIL: [info@porta-air.com](mailto:info@porta-air.com)

[www.porta-air.com](http://www.porta-air.com)

